

			Appr. Weight Per Linear Foot			
			Corrugated Style			
Diameter	Thickness	Guage	2 2/3 x 1/2	3 x 1	5 x 1	Spiral Rib
12	0.064	16	10			
	0.79	14	12			
15	0.064	16	12			
	0.079	14	15			
18	0.064	16	15			15
	0.079	14	18			18
21	0.064	16	17			17
	0.079	14	21			21
	0.109	12				29
24	0.064	16	19			19
	0.079	14	24			24
	0.109	12				36
30	0.064	16	24			24
	0.079	14	30			30
	0.109	12				42
36	0.064	16	29			29
	0.079	14	36			36
	0.109	12	49			50
	0.138	10	62			
42	0.064	16	34			33
	0.079	14	42			42
	0.109	12	57			58
	0.138	10	72			
48	0.064	16	38			38
	0.079	14	48			48
	0.109	12	65			66
	0.138	10	82			
	0.168	8	100			
54	0.064	16	44	50	44	43
	0.079	14	54	61	54	54
	0.109	12	73	83	73	75
	0.138	10	92	106	93	
	0.168	8	112	129	114	
60	0.064	16		55	48	48
	0.079	14	60	67	59	60
	0.109	12	81	92	81	99
	0.138	10	103	118	104	
	0.168	8	124	143	126	
66	0.064	16		60	53	53
	0.079	14	65	74	65	66
	0.109	12	89	101	89	91
	0.138	10	113	129	114	109
	0.168	8	137	157	138	

72	0.064	16		66	58	
	0.079	14		81	71	72
	0.109	12	98	110	97	99
	0.138	10	123	140	123	119
	0.168	8	149	171	150	
78	0.064	16		71	62	
	0.079	14		87	77	78
	0.109	12	105	119	105	108
	0.138	10	133	152	134	129
	0.168	8	161	185	163	
84	0.064	16		77	68	
	0.079	14		94	83	84
	0.109	12	113	128	113	116
	0.138	10	144	164	144	139
	0.168	8	173	199	175	
90	0.064	16	121	82	72	
	0.079	14	154	100	88	
	0.109	12	186	137	121	124
	0.138	10		175	154	149
	0.168	8		213	187	
96	0.064	16		87	77	
	0.079	14		107	94	
	0.109	12		147	129	132
	0.138	10	164	188	165	158
	0.168	8	198	228	201	
102	0.064	16		93	82	
	0.079	14		114	100	
	0.109	12		155	136	141
	0.138	10		198	174	168
	0.168	8		241	212	
108	0.064	16		98	86	
	0.079	14		120	106	
	0.109	12		165	145	150
	0.138	10		211	186	175
	0.168	8		256	225	
114	0.064	16		104	92	
	0.079	14		127	112	
	0.109	12		174	153	
	0.138	10		222	195	
	0.168	8		271	238	
120	0.064	16		109	96	
	0.079	14		134	118	
	0.109	12		183	161	
	0.138	10		234	206	
	0.168	8		284	250	

126	0.079	14		141	124	
	0.109	12		195	172	
	0.138	10		247	217	
132	0.079	14		148	130	
	0.109	12		204	180	
	0.138	10		259	228	
	0.168	8		314	276	
138	0.079	14		154	136	
	0.109	12		213	187	
	0.138	10		270	238	
	0.168	8		328	280	
144	0.109	12		223	196	
	0.138	10		262	248	
	0.168	8		344	303	